

## SPECIFICATION

## TITLE of INVENTION

5        Electronic Volume Measuring Equipment  
Guy A. Dickes  
Baltimore, MD  
410-484-0672  
US Citizen

10

## CROSS REFERENCE to RELATED APPLICATIONS

Not applicable

## STATEMENT REGARDING FEDERALLY SPONSORED RESEARCH or

15        DEVELOPMENT

Not applicable

REFERENCE TO SEQUENCE LISTING, TABLE, OR COMPUTER LISTING  
COMPACT DISK

20

Not applicable

## BACKGROUND of the INVENTION

Electronic Volume Measuring Equipment originated in response to the needs of the Post-Tensioning industry within the construction industry. In the late 1990's it was determined that previously approved construction techniques, materials, engineering and inspection used in the cement grouting of hollow ducts used in the post-tension industry were substandard. These ducts are used to carry post-tensioned steel reinforcing strand from one end of a concrete structure to the other providing active reinforcement to the concrete. Such structures include bridges, buildings and tanks. After the installation of the post-tensioning strand is completed, the ducts are filled with a fluid cementitious

25  
30

Electronic Volume Measuring Equipment    Application Number 10/614,173  
Guy Dickes 410-484-0672  
Page 1    Original submittal with marked up changes 7/12/2004

grout to provide structural capacity and more importantly, corrosion protection for this reinforcing steel.

5 Routine inspection of bridges, particularly in Florida, uncovered substantial corrosion related defects and failures of the reinforcing steel. This steel is active reinforcement, under many thousands of pounds of force and literally holds the bridge together. Failure of this steel can result in catastrophic collapse. Further in-depth investigation by numerous state Departments of Transportation and independent engineering firms have uncovered widespread problems throughout the post-tensioned bridge construction industry

10

Examples of these structures include:

Sunshine Skyway Bridge, Tampa, Florida

Central Artery, Boston, Massachusetts

Airport Parking Garage, Raleigh Durham, North Carolina

15

Mid-Bay Bridge, Pensacola, Florida

20

To understand the problem in basic terms, the cementitious grout materials used to fill the ducts bled (separated into cement and water) and shrank, creating voids in the ducts and behind the anchorages for the post-tensioned steel. It is in these areas that corrosion can occur. Major structural damage caused by corrosion ~~had~~ *has* been uncovered.

As part of an ongoing industry process, inspections are being conducted by many, if not all, state Departments of Transportation of these structures. Repairs are being instituted.

25

As part of the repair process, it is necessary to quantify the volume of the voids, both in the ducts and behind the anchorages. It is necessary to understand that many of these voids cannot be visually inspected or opened. The repairs must be conducted 'in the blind'. Thus it is necessary to quantify the extent of the problem using some sort of external testing equipment. Often, the only access to the voids is through a 1/2 inch hole, making visual inspection and conventional repair nearly impossible.

30

Much of the post-tensioning technology comes from Europe (France, Germany and Switzerland). The three main manufacturers of this equipment in the United States have ties to their European counterparts.

5 The equipment used by the European construction community to determine the volume in voids is a mechanical analog air measuring device first designed in the 1970's-1980's. The equipment in use today was built at that time.

Additional uses of this *electronic volume measuring equipment* include identifying unused volume in partially filled fuel tanks or chemical containers, pressure vessels, sealed piping systems, and other air tight systems. The need arose to have  
10 modern electronic equipment; easier to use, smaller and more efficient. This has been invented by Guy Dickes, Baltimore, Maryland USA.

#### BRIEF SUMMARY of the INVENTION

15 Electronic Volume Measuring Equipment utilizes electronic gas mass flow technology in a manner to provide accurate volume measurement of air tight containers, voids in concrete, other air tight structures and ~~containers~~ *piping systems* and tanks. There are three variations of the process.

The first process involves pumping air (or other pressurized gas) through the  
20 device into the void or container.

The second involves evacuating air from the void or container, and allowing air to rush back into the void through the device to measure volume.

The third involves evacuating air from the void or container through the device to measure volume.

25 The advantages of the Electronic Volume Measuring Equipment include portability and accuracy; one version fits into a 26 inch by 10 inch by 10 inch tool box. Another version fits within a 20 inch by 10 inch by 8 inch NEMA4 electrical box. Accuracy is approximately 99%. In contrast, the European mechanical model weighs several hundred pounds, requires a rolling platform for support and its accuracy is  
30 suspect. There are no other known means of determining blind volumes

Other advantages include ease of use and speed of results. The connection of the device to the void or container is via a *small diameter (typically 3/8 inch or 1/2 inch) hose 11 and the manifold or entrance valve is opened.* Direct reading of the volume is attained from the digital output meter 9. The European equipment requires 1 inch hose and  
5 requires interpretation of an analog gauge and needles and scales.

Other uses include measuring barrels and casks, fuel tanks, storage containers, piping systems. Inert gases can be used in lieu of air for fuel tanks or other pressure vessels containing explosive or hazardous materials.

#### 10 BRIEF DESCRIPTION of the SEVERAL VIEWS of the DRAWINGS

The drawings attach reflect the three current versions of the Electronic Volume Measuring Equipment.

- Drawing 1: Basic Equipment Lay-Out and Usage (Pressure Version)  
15 *Step 1A- Void or container at ambient pressure*  
*Step 1B- Void or container at partial pressure*  
*Step 1C- Void or container at full pressure*
- Drawing 2: *Process One: Specific Internal Component Layout (Pressure*  
20 *Version using Compressor)*
- Drawing 3: *Process One: Specific Internal Component Layout (Pressure*  
*Version using Compressed Gas)*
- 25 Drawing 4: *Process Two: Basic Equipment Lay-Out and Usage (Air Rushing*  
*Through Device into Evacuated Void or Container)*  
*Step 4A- Void or container fully evacuated*  
*Step 4B- Void or container at ambient pressure*
- 30 Drawing 5: *Process Two: Specific Internal Component Layout (Air Rushing*  
*Through Device into Evacuated Void or Container)*

Drawing 6: *Process Three:* Basic Equipment Lay-Out and Usage  
(Vacuum Drawn through Device)

5 Drawing 7: *Process Three:* Specific Internal Component Layout  
(Vacuum Drawn through Device)

#### DETAILED DESCRIPTION of the INVENTION

10 The Electronic Volume Measuring Equipment utilizes commercially available electronics and mechanical components in a manner differently than the purpose for which that equipment was originally designed.

There are ~~two-three~~ primary components and numerous secondary *support* components of this equipment. The primary components are the gas mass flow sensor 8  
15 ~~and the digital read-out meter 9 and the pressure regulator 6~~. The remaining components provide protection of the equipment and ~~pressurized gas or vacuum~~ *controlled flow through the apparatus*.

The primary equipment includes an electronic gas mass flow sensor 8 that measures the ~~volume mass~~ of a gas passing through it. It is designed to measure gas flow  
20 rate rather than volume. This mass flow ~~meter~~ *sensor 8* is connected electronically to a 'totalizer' digital read-out *meter 9*, to provide total gas mass, rather than gas flow rate. This equipment is typically used in an industrial or laboratory environment to measure gas volume.

By utilizing this equipment, and regulating pressure, volume determinations can  
25 be made of an air tight container or void. *'Boyles Law', discussed later, is the principal physic law in operation.*

#### MAJOR PARTS, Description and Usage

30 Air Intake Filter 1: *pleated paper type air filter to remove particulate dust (secondary)*

- Compressor 2: electric or hydraulic powered air device to compress air or other gas to pressures greater than 1 atmosphere greater than ambient pressure (*secondary*)
- Condensate Filter 3: device used to remove condensed moisture from compressed air (*secondary*)
- Desiccant Filter 4: device using silica gel or similar material to further remove moisture from the compressed air (*secondary*)
- In-Line Particulate Filter 5: filter designed to remove fine dust created by desiccant filter from the air (*secondary*)
- Pressure Regulator 6: high accuracy device designed to provide controlled, constant air or gas pressure to the system (*primary*)
- Flow Controller 7: needle valve assembly or similar device used to restrict air flow through the gas mass flow sensor to its design rating (*secondary*)
- Mass Flow Sensor 8: electronic device designed to measure the mass of gas flowing through and transmitting this information using a variety of outputs to the digital read-out meter 9 (*primary*)
- Digital Read-out Meter 9: electronic device that accepts output from the mass flow sensor 8 and totalizes flow readings into total volume and presents that information through a digital read-out panel display (*primary*)
- Vacuum Pump 10: electric or hydraulic device designed to reduce pressure in a void or container to near perfect zero pressure conditions (*secondary*)
- ~~Hose Entrance~~ Valve 11: devices to connect Electronic Volume Measuring Equipment to the void, container or tank to be measured entrance valve 12 (*secondary*)
- Entrance Valve 12: Device used to physically connect to the void or container to be measured 13 (*secondary*)
- Void or Container 13: That vessel that requires volume measurement
- Compressed Gas Cylinder 14: Vessel used to provide pressurized gas in lieu of air compressor 2 (*secondary*)

Electronic Volume Measuring Equipment Application Number 10/614.173

Guy Dickes 410-484-0672

Page 6 Original submittal with marked up changes 7/12/2004

PROCESS ONE: Pressurizing the Void or Container 13 using Compressor 2 or

5 Compressed Gas 14:

The layout of components and sequence of operations is as follows (internal compressor):

Intake air filter 1> Compressor 2> Condensate Filter 3> Desiccant Filter 4> In-Line Particulate Filter 5> Pressure Regulator 6> Flow Controller 7> Mass Flow Sensor 8/Digital Read-out Meter 9> Hose 11> Entrance Valve 12> Void/Container 13

Alternate- using compressed gas:

Compressed Gas Cylinder 14> Pressure Regulator 6> Flow Controller 7> Mass Flow Sensor 8/Digital Read-out Meter 9> Hose 11> Entrance Valve 12> Void/Container 13

15 Air is drawn through the intake air filter 1 by the Compressor 2. This compressed air goes through the condensate filter 3 to remove excess moisture. The compressed air continues through the desiccant filter 4 to further remove moisture. The compressed air passes through the In-Line Particulate Filter 5 to remove any dust or desiccant particles. The compressed air is then reduced in pressure to one atmosphere (14.7 psi) by the

20 pressure regulator 6. This is the first step to providing accurate volume measurement. The controlled pressure air then goes through a flow controller 7 valve to match it with the capacity of the mass flow sensor 8. Finally, the air goes through the mass flow sensor 8 and into the void or sealed container 13.

The air is dried to improve accuracy through the mass flow sensor 8. The mass

25 flow sensor 8 uses a 4-20mA or similar output to provide an electronic signal to the digital read-out meter 9. The digital read-out meter 9 is calibrated to the mass flow sensor 8.

One atmosphere pressure (14.7 psi, 29.92 inches of Mercury, 760 torr, 1013 millibar) is used for simplicity. Direct reading of the air mass volume from the electronic

30 digital 9 is possible without calculation. Essentially, one 'volume' of air is going into void or container.

Added benefits of Process One is that leakage in the void or container can be identified using a solution of water and common household liquid soap applied manually or through spray apparatus. Leakage can also be identified audibly. An auxiliary port is provided to bypass the Mass Flow Sensor 8/Digital Read-out Meter 9 *for this purpose.*

5

PROCESS TWO: Allowing Air to Rush into the Evacuated Void or Container

The layout of components and sequence of operations is as follows:

Intake air filter 1> Desiccant Filter 4> ~~In-Line~~ Particulate Filter 5 > Flow  
10 Controller 7> Mass Flow Sensor 8/Digital Read-out Meter 9> Hose 11> Entrance Valve  
12> Void/Container 13

In Process Two, the void is evacuated using a high vacuum pump 10. After the void is evacuated, the entrance valve 12 is opened, allowing air to flow through the ~~equipment apparatus~~ as in Process One. Air at sea level is at 14.7 psi, providing nearly  
15 the same level of accuracy as with Process One. Again the Desiccant ~~filter~~ 4 and ~~In-Line~~ Particulate Filters 5 condition the air prior to going through the mass flow sensor 8.

PROCESS THREE: Evacuating Air through the Mass Flow Sensor 8

20 The layout of components and sequence of operations is as follows:

Container/Void 13> ~~In-Line~~ Particulate Filter 5 > Flow Controller 7> Mass Flow  
Sensor 8/Digital Read-out Meter 9 > Vacuum Pump 10

In Process Three, air in the void or container is drawn through the ~~In-Line~~  
25 Particulate Filter 5 and flow controller 7 prior to mass flow sensor 8 and finally the vacuum pump 10.

In all of the above processes, commercially available parts are utilized. Physical connections between components are either brass or plastic plumbing parts.

Calibration is necessary for Process One, as accurate pressure control is required.

30 A factory calibrated pressure gauge is used for establishing the one atmosphere pressure. A high accuracy pressure regulator 6 (error less than 0.1%) is used.



In all cases, the flow controller 7 is adjusted *or preset* to limit the gas flow through the mass flow sensor 8 to rate set by the manufacturer. This is accomplished by measuring volume over time. If necessary, the flow controller 7 is closed down to slow the volume of gas through the sensor 8. (The sensors typically have flow rates of 5 to 75  
5 200 liters per minute). The flow controller 7 is set such that the maximum flow through the *mass flow* sensor 8 is less than the maximum rate set by manufacturer.

The basic physical law to be applied is 'Boyle's Law' which states that:

"The volume of a fixed mass of gas varies inversely with its pressure at constant temperature".

10 As an example, if we double the pressure in the same container, we have doubled the mass. Since this invention, *in standard configuration*, is doubling the pressure from atmospheric pressure at sea level to plus 14.7 psi, we have added one volume of gas to the container.